



Product Name: SuperCal Humic

Updated: January 2015

Sections 1 & 2 – PRODUCT AND COMPANY IDENTIFICATION AND COMPOSITION AND INFORMATION ON INGREDIENTS

Manufacturer: Calcium Products, 2520 N. Loop Dr. #7100, Ames, IA 50010
Product Name: SuperCal Humic
Common Name: Gypsum, leonardite (humic substance), calcium lignin sulfonate
Chemical Type: Mineral ores, lignosulfonate
Emergency Contact: (800) 255-8196 (M – F, 7:30am – 4:30pm CST)
Poison Control: (800) 222-1222 (24 hrs)

Chemical Name	C.A.S. No.	Chemical Formula	OSHA PEL	% By Weight
Non-Hazardous				
Gypsum	10101-41-4	CaSO ₄ • 2H ₂ O	5 mg/m ³	85-90%
Leonardite	1415-93-6	None	10 mg/m ³	10-15%
Calcium lignosulfonate	8061-52-7	C ₂₀ H ₂₄ CaO ₁₀ S ₂	N/A	1-2%

Section 3 – HAZARDS IDENTIFICATION

DESCRIPTION: Black/gray granular mix with slight mineral odor.

HEALTH HAZARDS: May be irritating to the respiratory tract, eyes, and skin. Ingestion may cause gastrointestinal upset. Dust may contain respirable crystalline silica.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing respiratory, skin, or eye conditions.

EYE CONTACT: Direct contact with dust may cause irritation by mechanical abrasion.

SKIN CONTACT: Direct contact may cause irritation by mechanical abrasion. Not absorbed through skin.

INGESTION: If ingested, intestinal obstruction may occur if the material hardens, especially in the pyloric region.

INHALATION: Dusts may irritate the nose, throat, and respiratory tract by mechanical abrasion. Coughing, sneezing, and shortness of breath may occur following exposures in excess of appropriate exposure limits. See section 11 for additional inhalation hazard information.

Section 4 – FIRST AID MEASURES

EYES: In case of contact, immediately flush eyes with water for a minimum of 15 minutes. Warm water is recommended but cold water may be used.

SKIN: In case of skin contact, immediately rinse area with water. Cover irritated area with an emollient. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Seek medical attention if irritation persists.

INGESTION: Give 2-3 glasses of water and induce vomiting. Call a physician.

Product Name: SuperCal Humic

INHALATION: If a person inhales a large amount of nuisance dust, move exposed person to fresh air at once. Other measures are usually unnecessary. If irritation persists, seek medical attention.

Section 5 – FIRE FIGHTING MEASURES

FLASHPOINT: Not flammable. **FLAMMABLE LIMITS IN AIR:** Not flammable.

EXTINGUISHING AGENT: Use media suitable to extinguish the source of the fire.

UNUSUAL FIRE AND EXPLOSION HAZARD: None.

Section 6 – ACCIDENTAL RELEASE MEASURES

Environmental Precautions: Do not apply directly to waterways or bodies of water.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Use dry methods to collect spilled materials, and reuse clean materials. Avoid generating dust. Do not clean up with compressed air. Minimize dust by evacuating area downwind in the case of large spills. Store contaminated materials in dry, sealed plastic or non-aluminum metal containers. Residues on surfaces may be washed with water.

Section 7 – HANDLING AND STORAGE

Ensure proper ventilation, and respiratory and eye protection are used under dusty conditions. Dew point conditions or other conditions causing presence of moisture will harden gypsum during storage. Excessive particulate concentrations in workplace must be avoided even though it is inert and non-toxic.

Section 8 – EXPOSURE CONTROL & PERSONAL PROTECTION

RESPIRATORY PROTECTION: NIOSH approved particulate respirator if required.

EYE PROTECTION: Safety glasses with side shield, goggles, or face mask recommended.

SKIN PROTECTION: Long sleeves, cotton gloves recommended.

VENTILATION: Local exhaust ventilation recommended.

Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Black to gray granular mix with slight detectable odor.

DENSITY: 50 lbs/ft³ **pH:** 6.08

BOILING POINT: N/A **VAPOR PRESURE:** N/A

VAPOR DENSITY IN AIR: N/A **FLASH POINT:** Not flammable.

Product Name: SuperCal Humic

EVAPORATION RATE: Zero

SOLUBILITY IN WATER: Negligible.

Section 10 – STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: N/A

INCOMPATIBILITY (Materials to avoid):
Strong acids.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:
P_{ox}, SiF₄, and HF gases.

Section 11 – TOXICOLOGICAL INFORMATION

Calcium sulfate dihydrate

Exposure route: Inhalation, skin, and/or eye contact.

Target organs: Eyes, skin, respiratory system.

Acute Effect: Calcium sulfate dihydrate dust has an irritant action on mucous membranes of the respiratory tract and eyes. There have been reports of conjunctivitis, chronic rhinitis, laryngitis, pharyngitis, impaired sense of smell and taste, bleeding from the nose and reactions of tracheal and bronchial membranes in exposed workers.

Section 12 – ECOLOGICAL INFORMATION

No data available.

Section 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

May be disposed of as an inert solid in sanitary landfill or by other procedures in accordance with all federal, state, and local regulations. May be used as a supplement on land and on some agricultural products.

Section 14 – TRANSPORT INFORMATION

DOT HAZARD CLASSIFICATION: None

PLACARD REQUIRED: None

LABEL REQUIRED: Label as required by OSHA Hazards Communication Standard [29 CFR 1910.1200 (f)] and applicable state and local regulations.

Section 15 – REGULATORY INFORMATION

Product Name: SuperCal Humic

FDA: Product is manufactured for agricultural applications. As such, FDA regulations do not apply.

Section 16 – OTHER INFORMATION

CFR: US Code of Federal Regulations

DOT: Department of Transportation

IARC: International Agency for Research on Cancer

IDLH: Immediately Dangerous to Life and Health

NIOSH: National Institute for Occupational Safety and Health, US Department of Health and Human Services

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PEL: Permissible Exposure Limits

SARA Title III: Title III of the Superfund Amendments and Reauthorization Act, 1986

TLV: Threshold Limit Value

TWA: Time-weighted Average

FDA: Food and Drug Administration