

SuperCal Humic



**CALCIUM
PRODUCTS™**

PELLETIZED HUMIC BLEND

SuperCal Humic is a combination of naturally mined gypsum and leonardite shale. This blend is designed to provide calcium and sulfur nutrition with humic acid, which may increase micronutrient availability, and is pelletized to make handling and distribution quick and easy.

Manufactured &
Guaranteed by:
Calcium Products
Gilmore City Location
50602 330th Avenue
Gilmore City, IA 50541

Corporate Address:
Calcium Products
ISU Research Park
2520 N. Loop Dr., #7100
Ames, IA 50010



NET WT. 50 lbs/22.67 kg

Improve your soil quality with SuperCal Humic.

RECOMMENDATIONS

It is recommended that a complete soil test be taken to determine pH and nutrient levels before applying any material to the soil. Soil test data allow you to determine the most efficient, effective application rate.

Regular applications of SuperCal Humic will:

- Supply calcium and sulfur, vital nutrients for optimum plant growth.
- Reduce surface crusting of soils, improving water penetration and seedling emergence.
- Loosen heavy clay soils to improve rooting and water infiltration.
- Help remove sodium from soils, improving plant growth.

Application

For new turf

Apply 5 lbs. per 1,000 square feet before seeding or sodding. Water thoroughly after application.

For established turf

Apply 5 lbs. per 1,000 square feet each spring and fall. Water thoroughly after application.

For established trees and shrubs

Apply 1/4 cup at the base of the tree or shrub each spring and fall. Water thoroughly.

Typical Spreader Settings

Apply only as directed. Do not apply near water.
Suggested settings not intended to replace calibration.

Spreader	5 lbs/1000 sq. ft. (equivalent to 217.8 lbs/acre)	Spreader	5 lbs/1000 sq. ft. (equivalent to 217.8 lbs/acre)
Andersons 2000/SR (Cone 3)	O 1/2 @ 3 mph	Lely (WTR, WFR, HR, 1250) P IIC	7 1/2 @ 4.5 mph/450 RPM
Scotts R-8, R-8A (Cone 3)	N 1/2 @ 3 mph	Vicon (03 Series)	39 @ 4.5 mph
Lesco 020093 (Pattern 0.25)	G 1/2 @ 3 mph	Precision Brand	7 1/2 @ 3 mph
Lesco 705698 (Pattern 0.25)	17 @ 3 mph	Vigoro	4 1/2 @ 3 mph

Actual settings may vary and depend on spreader type, mode and condition of the spreader. Always check spreader rate and setting prior to application.
Bulk Density - 51 lbs/CF

Guaranteed Analysis

Calcium (Ca)	17%
Sulfur (S)	14%
14% Combined Sulfur	
Derived from mined gypsum.	
Calcium sulfate dihydrate (CaSO ₄ • 2H ₂ O)	75%
Derived from mined gypsum.	

ALSO CONTAINS NON-PLANT FOOD INGREDIENT

Humic Acid	10%
Derived from leonardite shale.	

Information regarding contents and levels of metals in this product is available on the internet at <http://www.aapfco.org/metals.htm>

ADDITIONAL STATE REGISTRATION INFORMATION

COLORADO
0-0-0 grade

VIRGINIA

Do not apply near water, storm drains, or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn/garden, and sweep any product that lands on the driveway, sidewalk, or street, back onto your lawn/garden.