17-297-4050

Oct 24, 2017
RECEIVED DATE
Oct 17, 2017

SEND TO **7294**



PAGE 1/3

Oct 24, 2017

13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 www.midwestlabs.com

CALCIUM PRODUCTS INC 2520 N LOOP DR STE 7100 AMES IA 50010-8279

REPORT OF ANALYSIS

For: (7294) CALCIUM PRODUCTS INC AG LIME

| | Leve | l Found | | Reporting | | Analyst- | Verified- |
|------------------------------|----------------------------|----------|----------------------|-----------|---------------------|-----------------|-----------------|
| Analysis | As | Received | Units | Limit | Method | Date | Date |
| Sample ID: WALKERS PIT | Lab Number: 2734024 | Date San | npled: 2017-1 |)-13 | | | |
| Moisture | | 9.2 | % | 0.1 | SM 2540 G-(1997) | bjs0-2017/10/19 | asl4-2017/10/20 |
| Calcium (total) | | 34.1 | % | 0.01 | MWL ME PROC 26 | cjm4-2017/10/18 | asl4-2017/10/20 |
| Magnesium (total) | | 0.23 | % | 0.01 | MWL ME PROC 26 | cjm4-2017/10/18 | asl4-2017/10/20 |
| Total neutralizing value (Ca | CO3 eq) | 91.7 | % | 0.1 | AOAC 955.01 | eas2-2017/10/18 | asl4-2017/10/20 |
| ECCE | | 70.5 | % | 0.1 | Calculation | Auto-2017/10/24 | Auto-2017/10/24 |
| % passing 4 sieve | | 100 | % | 0.1 | ASTM E 276-13 (mod) | rko9-2017/10/24 | asl4-2017/10/24 |
| % passing 8 sieve | | 98.8 | % | 0.1 | ASTM E 276-13 (mod) | rko9-2017/10/24 | asl4-2017/10/24 |
| % passing 20 sieve | | 89.3 | % | 0.1 | ASTM E 276-13 (mod) | rko9-2017/10/24 | asl4-2017/10/24 |
| % passing 30 sieve | | 83.6 | % | 0.1 | ASTM E 276-13 (mod) | rko9-2017/10/24 | asl4-2017/10/24 |
| % passing 60 sieve | | 62.0 | % | 0.1 | ASTM E 276-13 (mod) | rko9-2017/10/24 | asl4-2017/10/24 |
| % passing 80 sieve | | 53.2 | % | 0.0 | ASTM E 276-13 (mod) | rko9-2017/10/24 | asl4-2017/10/24 |
| % passing 100 sieve | | 49.3 | % | 0.1 | ASTM E 276-13 (mod) | rko9-2017/10/24 | asl4-2017/10/24 |
| % passing 200 sieve | | 36.7 | % | 0.1 | ASTM E 276-13 (mod) | rko9-2017/10/24 | asl4-2017/10/24 |
| % retained pan | | 36.7 | % | 0.1 | ASTM E 276-13 (mod) | rko9-2017/10/24 | asl4-2017/10/24 |

17-297-4050

Oct 24, 2017
RECEIVED DATE
Oct 17, 2017

SEND TO **7294**



PAGE 2/3

Oct 24, 2017

13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 www.midwestlabs.com

CALCIUM PRODUCTS INC 2520 N LOOP DR STE 7100 AMES IA 50010-8279

REPORT OF ANALYSIS

For: (7294) CALCIUM PRODUCTS INC AG LIME

| | Level Found | | Reporting | | Analyst- | Verified- |
|----------|-------------|-------|-----------|--------|----------|-----------|
| Analysis | As Received | Units | Limit | Method | Date | Date |

All results are reported on an AS RECEIVED basis.

For questions please contact:

Rob Ferris

Account Manager

rferris@midwestlabs.com (402)829-9871

17-297-4050

Oct 24, 2017
RECEIVED DATE
Oct 17, 2017

SEND TO **7294**



PAGE 3/3

Oct 24. 2017

13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 www.midwestlabs.com

CALCIUM PRODUCTS INC 2520 N LOOP DR STE 7100 AMES IA 50010-8279

REPORT OF ANALYSIS

For: (7294) CALCIUM PRODUCTS INC AG LIME

Detailed Method Description(s)

SM 2540 G

Analysis follows MWL WC 060 which is based on SM 2540 G. A sample is weighed placed in a vacuum drying oven to drive off the moisture and re-weighed. The sample is then placed in a muffle furnace at 550°C, cooled, and re-weighed. The residue remaining is the ash and the mass lost is the volatile matter.

ICP Analysis Fertilizers AOAC 985.01 (mod)

Analysis follows MWL ME 026 which is based on AOAC 985.01. Samples have been prepared using MWL WC 056 which is based on AOAC 957.02 using mineral acids and heat. Sample analysis involves moving the sample extract into the ICP where it is nebulized and introduced into the high temperature plasma which energizes the electrons of the dissolved minerals/metals. As the energized electrons of the minerals/metals return to ground state, energy is released as light. The emitted wavelength(s) and light intensities are used to identify and quantitate the minerals/metals in the sample

AOAC 955.01

Analysis follows MWL WC 039 which is based on AOAC 955.01. A sample is treated with an excess of acid and then back-titrated with a known base to a phenolphthalein end point

Calculation

Analytical results are entered into applicable formulas to provide a calculated result which is reported.

Wet Sieve

Sample analysis follows MWL WC 070 which is based on ASTM E 276. A known mass of a solid is obtained and a pre-determined set of sieves obtained. The sample is placed on the upper most (largest screen size) and the sample washed with water to wash the materials through the sieves. The material retained on the individual sieves is removed and weighed and the percent of the total passing through the sieve is calculated and reported.

Fertilizer Prep AOAC 957.02

Samples are prepared using a combination of nitric acid and heat. The heating takes place in a block digestor